

222 Broadway New York, NY 10038 (800) 205-7216 thriveagritech.com info@thriveagritech.com



Pinnacle LED Light

Pinnacle maximizes plant growth and yield in warehouses and greenhouses


APPLICATIONS & FEATURES

Indoor cannabis flowerGreenhouse supplemental light0-10V dimmingSimple installation and wiring with external driverPassive cooling (no fans or water)5-Year Warranty


SPECIFICATIONS

Part number: PCL-600W-FS2	
600W	
2.8 µmols/joule efficiency	
1,680 µmols/sec light output	
Weight 13.2 lbs (6.0 kg)	
110V-277V or 347V-480V	
Power Factor > 0.9	
IP66, ETL, UL8800	
40,000 Hour Lifetime (Q90/B20)	
35C max ambient temperature	


FULL SPECTRUM WHITE



BEAM ANGLE: 120 DEGREES



DIMENSIONS





222 Broadway New York, NY 10038 (800) 205-7216 thriveagritech.com info@thriveagritech.com

Pinnacle LED Light

WIRING & INTERCONNECTION

Pinnacle lights can be electrically connected with interconnection cables for both power and dimming. See installation manual for detailed instructions.



MAXIMUM DAISY-CHAIN

Max # of connected lights	Current / Fixture
3	5.00A
5	2.90A
6	2.50A
6	2.17A
8	1.73A
10	1.25A
	3 5 6 6 8

LIGHTING LAYOUTS

Lighting layouts for a variety of horticulture applications are available, if you need a customized lighting layout please contact our customer support team. (800) 205-7216 • thriveagritech.com • info@thriveagritech.com



THRIVE