

(800) 205-7216 thriveagritech.com info@thriveagritech.com



# Infinity XE

Infinity XE is an easy-to-install, high efficiency LED grow light with a spectrum optimized to increase plant biomass and crop yields.

### **APPLICATIONS & FEATURES**

Cannabis veg up to 500 µmols/m²/sec

Multi-tier leafy greens 200-300 µmols/m<sup>2</sup>/sec

Propagation 50-150 µmols/m<sup>2</sup>/sec

0-10V dimming

Simple wiring and daisy-chaining

5-year warranty

# **SPECIFICATIONS**

Part Number: TBAR-60W-FS2

60W Input Power, 168 µmols/sec Light Output

2.8 µmols/joule Efficiency

Weight: 3.8 lbs. (1.7 Kg)

120V-277V Input Voltage

Power Factor > 0.9

IP66, ETL, CE, UL8800, DLC Listed


40,000 Hour Lifetime (Q90/B20)

40C max ambient temperature

### **BEAM ANGLE 120 DEGREES**



### **FULL SPECTRUM WHITE**



### **DIMENSIONS**

**⊢** 2.2″ **⊣** 

44.9 inches (1,140mm)







(800) 205-7216 thriveagritech.com info@thriveagritech.com









# Infinity XE **LED Light Bar**

### **DIMMING**

0-10V dimming from max intensity to off.



# WIRING & INTERCONNECTION

Infinity XE LED light bars can be electrically connected end-to-end or with an interconnection cable. See the installation manual for detailed instructions.



### **MAXIMUM DAISY-CHAIN**

Voltag	11101	x # of nected	Current/ Fixture
120	)	14	0.54 A
240	)	31	0.25A
277	,	35	0.22A

### **MOUNTING**

**FLUSH MOUNT** 

SUSPENSION MOUNT

### LIGHTING LAYOUTS

Lighting layouts for a variety of horticulture applications are available, if you need a customized lighting layout please contact our customer support team. (800) 205-7216 • thriveagritech.com • info@thriveagritech.com

